



Who We Are

Smart lighting company established in 2016 as a lighting solution provider working with the projects from the designing phase passing through the products estimation till installing it on the site.

Based in the Egyptian market specialized at energy saving field by using led lighting systems, as we have factory that making over 50% of our products in Egypt with high quality according to universality specifications.

Smart lighting company is dealing with the elite of international companies specialized at the lighting systems, like (Cree - Osram - Schwabe - Bridgelux - Phillips - Samsung) in manufacturing chips field with both type (COB - SMD) and (Phillips - Meanwell - Schwabe - Tridonic) on manufacturing drivers.





Our Vision


"To pioneer Egypt's LED lighting sector with cuttingedge, sustainable solutions, enriching lives and setting new benchmarks in the industry."

Our Mission

- Our mission is to make and sell the latest version of led lighting systems, we believe that light is a part of every thing and its knowledge should be shared through our products and services.
- Highly qualified employees will bring both saving and safety to our valuable customers in the Egyptian market.
- With one of the strongest sales teams we will hit the numbers and keep our growth of profitability on the highest level.



CODING SYSTEM



Outdoor Lighting





Bulk Head

SLT-B01-LED Cow Eye



PERFORMANCE DATA

Efficacy: 116 Lm/W

Input Voltage: 220 - 240V

Frequency: 50Hz

Color Rendering: CRI 80

Color Temperature: 3000K

Life Time: 50.000 hrs.

Optic: 120°

Class: III

MECHANICAL SPECIFICATIONS

Material: Aluminum & Plastic

Mounting: Surface / Wall Mounted

Lens: Opal Finish: Black

Protection Class: IP 65

Mechanical Resistance: IK 03
















Code	Power W	Efficacy Lm/W	Colour Temp.	Dimensions WxPxH mm	Driver	LED Chip	Weight Kg
BO13308XXXLXXXX	10 12	116	3000 4000 6500	182x280x90 mm	Elsewedy Done	Lumiled	0.950





CUSTOMISZE OPTIONS



4K

6.5K

CRI >80

DALI


IK10

Light Light Temperature Temperature Temperature 3000K 4000K

Light 6500K

Color Rendering Index >80

POLAR CURVE



Bulk Head

SLT-B03



Efficacy: 80 Lm/W

Input Voltage: 220-240VAC

Frequency: 50-60 Hz

Color Rendering: CRI 80

Color Temperature: 3000K

Life Time: 50.000 hrs.

Optic: 120°

Class: III

MECHANICAL SPECIFICATIONS

Material: Aluminum & Plastic

Mounting: Surface / Wall Mounted

Lens: Plastic Finish: Black

Protection Class: IP 65

Mechanical Resistance: IK 03
















Code	Power W	Efficacy Lm/W	Colour Temp.	Dimensions LxWxH mm	Driver	LED Chip	Weight Kg
B032308XXXLX013	13	80	3000	280x182x85 mm	CE El-Sewedy	Lumiled	





CUSTOMISZE OPTIONS







6.5K








Light Light Light Temperature Temperature Temperature 3000K 4000K 6500K

Color Rendering Index >80

POLAR CURVE





Plafonira

SLT-2415



Efficacy: 95 Lm/W

Input Voltage: 220 - 240V

Frequency: 50-60Hz

Color Rendering: CRI 80

Color Temperature: 3000K

Life Time: 50.000 hrs

Optic: 110°

Class: III

MECHANICAL SPECIFICATIONS

Material: Polycarbonate Body & Opal diffuser

Mounting: Surface / Wall Mounted

Lens: Opal Finish: White

Protection Class: IP 66

Mechanical Resistance: IK 08
















Code	Power W	Efficacy Lm/W	Colour Temp.	Dimensions WxP mm	Driver	LED Chip	Weight
24151XXXXXXXOTXXX	10 15 20 24	95	3000	260x87 mm	Osram	Tridonic	





CUSTOMISZE OPTIONS



3000K

4K



Light Light Light
Temperature Temperature Temperature 4000K



6500K




DALI

Color Rendering Index >80



POLAR CURVE





LED Strip

SLT-LS65-5M



PERFORMANCE DATA

Efficacy: 100 Lm/W

Input Voltage: 220 - 240V

Frequency: 50-60Hz

Color Rendering: CRI XX

Color Temperature: 3000K-4000K

Life Time: 50,000 hrs

Optic: 120°

Class: III

MECHANICAL SPECIFICATIONS

Material: Thermoplastic

Mounting: Suspended, Surface

Lens: Rubber

Finish: Black-White-Gray **Protection Class:** IP 65

Mechanical Resistance: IK 03















Code	Power W	Efficacy Lm/W	Colour Temp.	Length Roll	Driver	LED Chip	Weight
STRLEDXXXXW/M1P65	5 10	100	3000 4000	5000 mm	Meanwell	Osram	

Length

Driver

LED Chip

Weight



CUSTOMISZE OPTIONS

POLAR CURVE



Light

3000K



Light

Temperature Temperature Temperature

4000K



6.5K

Light

6500K




Color Rendering Index >80




DALI

White Gray





OUR SUCCESS PARTNERS



"Thank you for trusting Us"

At Smart Lighting, We deeply value the trust you've placed in Us. Your confidence drives us to continually improve, innovate, and deliver the best in smart lighting solution. Every partnership we build is a testament to our commitment to quality, reliability, and excellence.

We are dedicated to earning the trust of more customers by consistently offering cutting-edge technology personalized support, and lighting solutions that meet the highest standards. Thank you for being a part of our journey, and we look forward to lighting the way to a brighter future together.

Our Customers





















































































Our Customers

























SMART LIGHTING

- Address: Fourth Industrial Zone, PART 38., Badr City, Cairo

- Address: Fourth Indus
 (+2) 02 8605058
 (+2) 011 277 555 01
 (+2) 011 277 555 15
- info@smartlightingco.com
- (1) www.smartlightingco.com

